



Why Hong Kong?

- HK Strategic location for entering into the China market for building materials because...
 - Abundant feedstocks supplies from China, e.g. fly ash, slag, ...
 - More opportunities for "new" building materials
 - Features of Hong Kong:
 - Renowned worldwide financial centre
 - Intelligent properties (IPs) legal protection



NAMI - APPLIED R&D CENTRE FUNDED BY HK GOVERNMENT

Nurturing Hong Kong industry growth through demand driven innovative research models, e.g.


- Radical innovation
- Performance improvement of existing products
- Product customization regional feedstocks suppliers and regional market demands
- → Strategic partnership with local R&D entities



About NAMI

NAMI

- Established in 2006
- R&D Center funded by HK Government
- Focus on applied R&D



Mission

- Developing core competences in nanotechnology and advanced materials as part of a powerful technology platform that leads to a wide spectrum of innovative products;
- Acting as the focal point for conducting market-driven, demand-led R&D aiming at technology upgrading of regional enterprises;
- Training human resources in nanotechnology and advanced materials for the present and future needs of Hong Kong and the Pearl River Delta region.

Our Office & Laboratories





HKSTP












Our Research Team



Areas of Research

Chemistry/Chemical Engineering/Biochemistry

Material Science/Materials Engineering

Physics

Mechanical/Electrical/Electronic Engineering/Civil

Engineering

Biochemistry/Biotechnology/Environmental

Engineering

Universities

Hong Kong - HKU, CUHK, HKUST, HKBU, CityU, PolyU

Overseas - University of Toronto, University of Washington, University of Michigan, Yale University, Aston University, University of Bristol

PRC - Tsinghua University, Beijing University of Aeronautics & Astronautics, South China University of Technology



Market Sectors




JAMI Proprietary

M

DRIVING MARKET DEMAND DRIVEN AND INNOVATIVE COLLABORATIVE RESEARCH

- Demand driven collaborative research model increases commercial success of applied research
- Aligning NAMI and industrial partners' roadmap for long term collaboration






Intro of Construction & Building Materials Sector at NAMI



NAMI R&D in Building Materials



Why these FOUR focuses: In Hong Kong...


- Energy: 1/3 consumed electricity in HK due to air-conditioning
- Recycle: 55% waste recycling target by 2020
- Maintenance: 40+% buildings over 30 years requiring regular inspection & maintenance
- Noise: 600 roads generating 70+dB noise, neighborhood noise

- NAMI's focus: Smart & Sustainable Buildings Materials
- → Nano & advanced materials create innovative material with new features to cater the local market demands


Core Technologies of Construction & Building Materials Sector

☐ Core competencies: Advanced materials *formulations* & *processes* for various applications:

- Examples of cementitious materials: Foamed concrete, waterrepelling concrete, rapid-cure concrete, fibre reinforced cementitious materials, VOC-free coating, waterproof rendering, aggregates recycling, etc.
- Examples of polymeric materials: modified polymericcementitious waterproof coating, engineering plastics, etc.









Advanced Cementitious Materials

Structural-grade foamed concrete

- Compressive strength: >30MPa
- Thermal conductivity: <0.5 W/mK





Cementitious fibre reinforced matrix


- Contain 90% recycled materials
- Water resistance, saltwater resistance and alkali resistance





Impact sound insulation floor

- Self-compact
- 15+dB impact sound reduction



Geopolymer for rapid repair

- Rapid cure (2~4 hrs), 1/10 epoxy cost
- Applicable on wet surface








Advanced Coating for Buildings

Advanced thermal insulating coating

- Cement-based, VOC-free
- Achieved 16°C temperature difference under 0.5mm thick








Air Filled Green Material + Reflective Nanoparticles

Self-healing material

- C-S-H (Calcium Silicate Hydrate) based
- "Heal" ~100um cracks in concrete



2-in-1 anti-carbonation and pore-liner coating

- Hydrophobic, anti-carbonation
- 10 times better Cl & CO₂ resistance than market products



Coating penetration for enhanced surface protection





Rapid Repair Materials for Pavements in Hong Kong

Market Potentials of Rapid Repair Materials for Highways

- HK road network: 2,075km in total length, in which
 - Approx 75% are bitumen pavements, 25% are concrete pavement
- Typical design life:
 - Bitumen pavement: 20 years
 - Concrete pavement: 40 years



Advantage of Bitumen Pavement

- Why bitumen (flexible) pavement is more common in HK?
 - Less traffic impact caused by repair and maintenance.
 - However...
 - "...this approach (flexible pavement) is not necessarily cost effective, in particular when the oil price is on a far steeper rising trend in comparison with cement... maintenance difficulty of rigid pavement (concrete) may not be an insurmountable factor either, taking into account the state-of-the-art technology"

Guidance notes on pavement design for carriageway construction, Highway Department, HKSAR, Sept 2013





Common Rapid Repair Cementitious Concrete



- Superplasticizer with set accelerator
 - >6 local suppliers
 - Approx 12h for traffic open
 - 4~5 times costs of Portland cement
- Calcium sulfoaluminate cement (CSA)
 - >3 local suppliers
 - Approx 2h for traffic open
 - 6~12 times costs of Portland cement
 - Yet, due to its difficulties of quality control of on-site mixing, high cost, it is not recommended in HK

Compressive strength development of rapid hardening

Comparisons of Various Repair Materials for Highway

Material		Installation Temperature	Curing	Typical Material Properties						
	Thickness Limitations			Drying Shrinkage	Coefficient of Thermal Expansion	Compressive Strength (MPa)				Elastic
						2 Hrs	24 Hr	3 Days	28 days	Modulus (GPa)
Portland Cement Concrete	> 40mm	5 – 32°C	Wet 7 days	Moderate	7-12x10 ⁻⁶	0	5	20	40	23
Rapid Hardening Cementitious Concrete	> 50mm	5 – 30°C	Wet 2-12hrs	Moderate	8-20x 10 ⁻⁶	0-20	20-40	- 0	55-85	1-30
Polymer Concrete	>30mm	7 – 35°C	Wet 2-3hrs	Low	7-12x10 ⁻⁶	20	30	40	50	22
Epoxy Resin Mortar	>5mm	10 − 32°C	Air	Low	25-30x10 ⁻⁶	0	70	80	85	0.5-20
Polyester Resin Mortar	>5mm	0 - 60°C	Air	Low- Moderate	25-35x10 ⁻⁶	60	80	-	100	2-10


Source: Highway Department, HKSAR, Mar 2012

- Early strength (>20MPa, 2h) is achievable by both cementitious and polymeric materials.
- Coef. thermal expansion mismatch of polymeric mortar can be compensated by applying fabric inside, but the increased cost and quality control are of concern.

Lessons Learnt from Highway Department of Hong Kong

- Due to the increasing oil price and cementitious materials technologies advancement, the Gov't department has sufficient incentives to switch back to rigid (concrete) pavement.
- Rapid cure cementitious materials are strongly welcome by the department, as far as the minimum requirements can be achieved, i.e. 20MPa, 4h, and cost-effective.
- Yet, the "new" materials to be adopted by the department have to be commonly available in the market for the Gov't to include them into the procurement specs, e.g. more than one supplier.

Strategy of Introducing New Materials for Construction & Building Industries



What NAMI is Doing on Geopolymer?

- NAMI has just received approval from HK Gov't working on geopolymer, target for rapid repair for concrete pavement and underground sewage ducts repair.
- This 16 months project is targeted to be started from Sep 2014.
- Collaborations with universities/institutes and industries are welcome.
- Graduates with related background are strongly welcome to join us.

Facilities Available at HKUST-NAMI











NAMI Proprietary

NAMI Your Materials Expert



納米創意無止境